Mounting Channels



Universally slotted mounting channel profile

Material specifications				
Material	DX51D or Equivalent steel DD11 or Equivalent steel			
Coatings	Galvanized, Hot-Dip Galvanized (HDG), Powder Coating*, Zinc Magnesium*			




Applications

- Installation of light to medium-duty ventilation ducts, plumbing & firefighting pipes and cable trays
- Secondary support structure for installation of different services.

Features & Benefits

- Wide range of mounting options in conjunction with our FXC mounting channel accessories.
- Quick and efficient attachment of multiple support structure.
- Lateral and vertical adjustment with reliable fastening.
- High load bearing capacity owing to special material properties and design.



Select Variant

Article No.		Product Description	L	w	н	t
Galvanized (vz)	HDG (fvz)	Product Description	(mm)	(mm)	(mm)	(mm)
300000	300001	FXC Mounting Channel 27/18/1.25, 6 m	6000	27	18	1.25
300010	300011	FXC Mounting Channel 27/18/1.25, 3 m	3000	27	18	1.25
300020	300021	FXC Mounting Channel 27/18/1.25, 2 m	2000	27	18	1.25
300030	300031	FXC Mounting Channel 27/18/1.25, 1 m	1000	27	18	1.25

*Available on request

in.fixotec.global | 01